



DESCRIPTION: 2040 PREMIUM WALL BASE ADHESIVE

Taylor 2040 is an off-white, hard-setting, acrylic adhesive formulated for the installation of rubber and vinyl cove base over wood, concrete, brick, plaster, wallboard or other porous surfaces. Exhibits fast tack and wet suction to hold on inner and outer corners. Will not contribute to staining, shrinkage or plasticizer migration. Note: Do not apply over non-porous surfaces such as vinyl wall coverings, laminated masonite, or plastic laminates.

SURFACE PREPARATION

Roughen glossy surfaces such as enamel paint and rinse alkaline surfaces with vinegar or acetic acid. The surface must be structurally sound, clean, level, dry, and free from dust, dirt, wax, grease, loose paint, plaster, and other contaminants that may interfere with proper bonding. Fill all holes and cracks with a cement based patching compound and sand high spots.

INSTRUCTIONS

Cove base should be laid out flat, and the room, cove base and adhesive should be 65°F (18.3°F) for 24 hours prior to, during, and after installation. Note: for best adhesion with molded rubber cove base, it is recommended to wipe the back with mineral spirits prior to installation.

1. Spread the adhesive on the back of the cove base with 3/32" x 3/32" x 3/32" (2.4mm x 2.4mm x 2.4mm) V-notch trowel or cartridge gun, to leave an ample amount of adhesive for the wall surface.
2. The cove base can be set in place up to 15 minutes after the adhesive is spread. Press firmly to the wall and rub or roll towards previously installed cove base. This will give a smooth, even bond with no gaps at the seams. Check to see that the adhesive has proper transfer to the wall.
3. Clean-Up: Use warm soapy water while adhesive is still wet. If dried, use Taylor Touchdown #9 Adhesive Remover/Stripper.

PHYSICAL PROPERTIES

Base:	Acrylic Latex
Appearance:	Off-white, heavy paste
Open Time:	Up to 30 minutes
Shelf Life:	One year in unopened container at 70 degrees F.
Coverage:	Up to 280 linear feet of 4" cove base per gallon.
Other Features:	Freeze-thaw stable to 10°F. Made with anti-microbial agents that will provide its dry film with protection from fungal growth. This protection is determined using the ASTM G21 test method.
Flammability:	Non-flammable. Meets Class 1 ratings as determined by ASTM E-84.

CAUTION: DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY INFORMATION: This product is manufactured according to exacting quality control standards and is warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control. For complete warranty information, call Taylor Technical Services at 800-868-4583; e-mail us at info@wftaylor.com, or visit www.wftaylor.com.

W.F. TAYLOR CO., INC. * FONTANA, CA 800.397.4583 * DALTON, GA 800.868.4583

TAYLOR 2040

MATERIAL SAFETY DATA SHEET

SECTION I IDENTIFICATION

Manufacturer's Name: W.F. Taylor Co., Inc.
Address/Phone: 11545 Pacific Ave.
Fontana, CA 92337
951.360.6677
Emergency Phone No.: 800.535.5053
Product Class: Synthetic Latex Blend
Manufacturer's Code Identification: 2040
Trade Name: 2040 Premium Cove Base Adhesive
Date Revised: 01/26/11

SECTION II HAZARDOUS INGREDIENTS

None per OSHA Regulation: 29 CFR 1910.1200
SARA Title III Section 313 Chemicals: None

NFPA	HMIS
	H = 1
	F = 0
	R = 0

SECTION III PHYSICAL DATA

Boiling Point: No data
Lbs/Gal: 9.5 – 11.5
Evaporation Rate/Vapor Density: Same as water.
Vapor Pressure: Same as water
Solubility in Water: Dilutable
Percent Volatile: 41 - 44 (by weight)
Color: Off White
Odor: Mild

SECTION IV FIRE AND EXPLOSION HAZARD DATA

DOT Category: Not regulated
Flash Point: None
LEL: N/A
Extinguishing Media: None required
Unusual Fire and Explosion Hazards: None
Special Fire Fighting Procedures: None

SECTION V HEALTH HAZARD DATA

Symptoms of Over Exposure:

Inhalation: May cause slight irritation to the upper respiratory tract
Eyes: Vapor may cause irritation
Skin: May cause slight skin irritation
Ingestion: Not a likely route of entry under proper handling conditions. May cause vomiting. Symptoms may be same as inhalation.

First Aid Procedures:

Eyes: Flush with water
Skin: Wash with soap and water
Inhalation: Remove to fresh air if needed
Ingestion: Do not induce vomiting. Call physician immediately

SECTION VI REACTIVITY DATA

Stability: Stable

Conditions to avoid: None known

Incompatibility/Materials to avoid: None known

Hazardous decomposition products: None known

Hazardous polymerization: Will not occur

SECTION VII SPILL OR LEAK PROCEDURES

Steps to Be Taken if Material is Spilled: Keep out of sewer systems to prevent blockage due to polymer deposits. Scrape up and contain for salvage or disposal.

Waste Disposal: Abide by all state, federal and local regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

Respiratory protection: None needed

Ventilation: Local exhaust

Protective gloves: None required.

Eyes: Goggles

Other protective equipment: None

SECTION IX SPECIAL PRECAUTIONS

Precaution for Handling and Storing: Do not puncture, protect from freezing and excessive heat.

KEEP OUT OF REACH OF CHILDREN



www.wftaylor.com