

DESCRIPTION: TOUCHDOWN[®] 710 KWIK SEAM LATEX ADHESIVE

Taylor 710 is a fast-drying, multi-use latex adhesive exceptionally effective for applying both plain webbing or pin type seaming tapes, replacing damaged carpet nap, securing carpet binding, patching carpets or other fabrics, sealing raw edges, reinforcing hand sewn seams and weak backings, coating the backs of throw rugs to reduce slipping hazards and many other purposes.

APPLICATION

Apply Kwik-Seam with small, clean brush or broadfelt scrap. Clean brush in water after using. Can be thinned with water. Note: care should be taken to avoid spilling Kwik-Seam on nap of carpet. Spillage may be removed if still wet by applying water and sponging until clean. Dried Kwik-Seam on carpet nap can best be removed with Touchdown #9 Adhesive Remover/Stripper.

DO NOT expose to heavy traffic for 24 hours.
DO NOT expose to water for at least 4 days.
DO NOT expose to standing water.

PHYSICAL PROPERTIES

Base: Natural latex.
Appearance: White pourable cream.
Odor: Ammonia-like
Coverage: Approximately 1,200 linear feet per gallon as a seam sealer.
Shelf Life: Six months in unopened container at 70° F.
Flammability: Non-flammable.
Other Features: Freeze/thaw stable to 10° F (-12.22° C).
Made with anti-microbial agents that will provide its dry film with protection from fungal growth. This protection is determined using the ASTM G21 test method.
Clean up: Clean up spills immediately. Avoid letting adhesive dry on the face of carpets. While wet, use water. If dried, use Taylor Touchdown #9 Adhesive Remover/Stripper.

CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

LIMITED WARRANTY

This product is manufactured according to exacting quality control standards and is warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control. For information, call Technical Services at 800-868-4583; visit us on the web at www.wftaylor.com; or e-mail us at info@wftaylor.com.