

DESCRIPTION: TOUCHDOWN® 720-C CARPET PADDING CEMENT

A fast tacking, synthetic rubber adhesive, formulated to bond carpet padding to floors rapidly to facilitate the installation of carpet. May be used on all types of sponge rubber, foam rubber, primed and bonded urethane, as well as all jute and hair carpet pads. Normally used under both sides of all seams, around perimeter and in selected field areas where needed.

DIRECTIONS

Normally applied to clean, dust free floors directly from this can by punching several holes in the inner cap and laying down a ½" bead in the areas to be bonded. Spread this bead with a spreader or scrap of cardboard, carpet backing or other object. In most weather conditions, this adhesive will then dry to a strong tacky state in a matter of minutes. Lay the padding into the tacky adhesive and press down. Then proceed with the installation.

DANGER – EXTREMELY FLAMMABLE - FOR PROFESSIONAL USE ONLY!

Extremely flammable! Toxic! Vapors may ignite explosively. Prevent buildup of vapors – open all windows and doors, use only with cross ventilation. Keep away from heat, sparks, and open flame. DO NOT smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors, and all other sources of ignition during use and until all vapors are gone. Close container after use. KEEP OUT OF REACH OF CHILDREN. Harmful or fatal if swallowed. If swallowed, DO NOT induce vomiting. Call a physician immediately. Avoid breathing vapors. Avoid prolonged or repeated contact with skin or contact with eyes. Contains Aliphatic Hydrocarbons and Toluene. Do not store at temperatures above 120° F, or in direct sunlight. Do not incinerate container.

CALIFORNIA PROPOSITION 65: WARNING

This product contains Toluene, a chemical known to the State of California to cause birth defects or other reproductive harm.

PHYSICAL PROPERTIES

Base: Synthetic Rubber, resin blend
Appearance: Thin amber color syrup
Odor: Ester like odor
Coverage: Approximately 500 square feet per gallon.
Shelf Life: One year in unopened container at 70° F
Flammability: Flammable
Other Features: Non photo-chemically reactive per rule 102. Freeze/thaw stable to 10° F (-12.22° C).
Clean up: Clean up spills immediately. Avoid letting adhesive dry on the face of carpets. If dried, use Taylor Touchdown #9 Adhesive Remover/Stripper.

LIMITED WARRANTY

This product is manufactured according to exacting quality control standards and warranted to be free of manufacturing defects. Defective materials called to our attention within one year from manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control.

W.F. TAYLOR CO., INC. * FONTANA, CA 800.397.4583 * DALTON, GA 800.868.4583