

DESCRIPTION: TOUCHDOWN 757C ALL WEATHER OUTDOOR CARPET ADHESIVE

Taylor 757C is made for the permanent outdoor installation of outdoor carpets – needle punched, artificial grass, ActionBac or Unitary Back. DO NOT USE ON VINYL, URETHANE OR EXPANDED STYRENE BACKINGS. Sets rapidly, even in cold weather. May be applied at temperatures as low as 40°F. This adhesive is waterproof and unaffected by rain and snow. DO NOT USE INDOORS OR IN ENCLOSED AREAS.

USE OVER: May be applied over wood, concrete, or firm asphalt surfaces.

APPLICATION: Use a 1/8" x 1/8" x 1/8" U notched trowel for most carpet backings. For the best bonds, the trowel notches must be large enough for the adhesive to make good contact with recessed areas of the backing.

Not recommended for bonding non-porous products to non-porous surfaces as the solvent cannot escape, therefore the adhesive cannot set. When installing nearly non-porous unitary-backed goods to non-porous surfaces, let the adhesive “tack-up” until it will make two inch “legs” when finger tested.

Complete the installation by rolling the carpet with a light weight roller or carpet core to make certain the adhesive makes deep contact into the carpet backing.

DANGER: EXTREMELY FLAMMABLE

FOR PROFESSIONAL USE ON OUTSIDE INSTALLATIONS ONLY! Extremely flammable! Toxic! Vapors may ignite explosively. Prevent buildup of vapors. Use only with cross ventilation. Keep away from heat, sparks, and open flame. DO NOT smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone. Close container after use. KEEP OUT OF REACH OF CHILDREN. Harmful or fatal if swallowed. If swallowed, DO NOT induce vomiting. Call a physician immediately. Avoid breathing vapors. Avoid prolonged or repeated contact with skin or contact with eyes. Contains petroleum distillates, toluene, and methyl acetate. Flash point of this adhesive is 8.6°F T.C.C.

PHYSICAL PROPERTIES

CA Proposition 65: This adhesive contains chemicals known to the State of California to cause birth or reproductive defects.
Base: Synthetic rubber, resin blend
Appearance: Soft medium viscosity, light color
Odor: Ester like odor
Open Time: Up to 30 minutes, depending on sun, heat, and wind conditions
Coverage: 50-100 sq. feet per gallon depending on the trowel used and the porosity and texture of the substrate
Shelf Life: One year in unopened container at 70°F
Other Features: Waterproof. Freeze/thaw stable to 10°F (-12.22°C). Non-photochemically reactive per rule 102.
Clean up: Taylor Touchdown #9 Adhesive Remover / Stripper

LIMITED WARRANTY

This product is manufactured according to exacting quality control standards and is warranted to be free from manufacturing defects. Product proven to be defective and called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control. There may be backings and surfaces to which this adhesive may not adhere. It is the user's responsibility to do a test patch to determine suitability of the bond. For information, call Technical Services at 800-868-4583; visit us on the web at www.wftaylor.com; or e-mail us at info@wftaylor.com.