

DESCRIPTION: TOUCHDOWN® NO. 775-C SEAM CEMENT

Recommended for seaming selvage edge and cross joints on most carpets including sponge and foam-backed carpet.

Not recommended for vinyl-backed carpets. Non-photochemically reactive per rule 102.

APPLICATION - FOR PROFESSIONAL USE ONLY

1. Cement is ready for use. Pour into polyurethane squeeze bottle.
2. Apply a 1/8" bead of adhesive along the entire edge of the "primary" back on one piece of carpet to be seamed. Butt the other piece of carpet to be seamed to the first piece for proper adhesive transfer and to secure the seam.
3. Excess seam cement that has dried can be removed by rubbing with a clean white rag dampened with Taylor Touchdown #9 Adhesive Remover/Stripper.
4. Return seam cement to the container after use. Do not store in plastic squeeze bottle.

PHYSICAL PROPERTIES

Base: Synthetic Rubber, Resin Blend
Appearance: Thin straw color syrup
Odor: Ester like odor
Coverage: Up to 1,000 linear feet per gallon.
Tracer: Does not contain fluorescent tracing agents
Shelf Life: One year in unopened container at 70°F.
Clean-Up: Taylor Touchdown #9 Adhesive Remover/Stripper

DANGER: EXTREMELY FLAMMABLE! FOR PROFESSIONAL USE ONLY

TOXIC! VAPORS MAY IGNITE EXPLOSIVELY. Prevent build-up of vapors. Open all windows and doors. Use only with cross ventilation. Keep away from heat, sparks and open flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone. Close container after use. **KEEP OUT OF REACH OF CHILDREN!** Harmful or fatal if swallowed. If swallowed, do not induce vomiting. Call Physician immediately. Avoid breathing vapors. Avoid prolonged or repeated contact with skin or contact with eyes. Contains, Toluene, N-Hexane, and Methyl Acetate. Complies with Consumer Product Safety Commission ban on extremely flammable contact cements. Flash point of this cement is over 20° F.T.O.C.

WARNING

This product contains Toluene, a chemical known to cause birth defects or other reproductive harm.

LIMITED WARRANTY

This cement is manufactured according to exacting quality control standards and warranted to be free of manufacturing defects. Product proven to be defective and called to our attention within one year from manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control.

W.F. TAYLOR CO., INC. * FONTANA, CA 800.397.4583 * DALTON, GA 800.868.4583