

DESCRIPTION: 8300 ONE FLOOR SOLVENT-FREE CARPET SEAM SEALER

Shaw 8300 provides a polymer fortified adhesive bond and is recommended for seaming all thermoplastic back carpets.

FLOOR PREPARATION

1. Prepare carpet according to manufacturer's instructions.
2. Apply a bead of sealer along the carpet backing edge with an adhesive applicator bottle. Apply adhesive to only one side of carpet.
3. Complete the seam by butting both sections of the carpet together while the adhesive is still wet (within 5-10 minutes).
4. To completely seal the installation, lift up the perimeter of the carpet and apply a ¼" bead around the perimeter of the room next to the wall and all stationary objects. Lay in the carpet over the sealer so the sealer makes contact with both carpet and wall or stationary object. When sealer is cured it will form an impervious barrier from topical moisture.
5. Smears of sealer on the surfaces are easily cleaned within 10 minutes by rubbing with a clean cloth wet with soapy water. Avoid soaking carpet with water. Do not pour soapy water directly on carpet.

PHYSICAL PROPERTIES

VOC's:	Negligible
Base:	Latex/polymer mixture
Color:	White
Odor:	Mild
Consistency:	Low viscosity
Shelf life:	One year in unopened container at 70° F.
Other Features:	Non-flammable.
Clean Up:	Warm soapy water when wet, Taylor Touchdown #9 Adhesive Remover/Stripper when dry.

HANDLING PRECAUTIONS

Use with sufficient ventilation. Use fans, motors and other equipment, open door and windows as necessary. Prevent prolonged or repeated breathing of vapors or mist. This product contains low levels of ammonia, which is not classified as an organic compound. Eye irritation and dizziness are indications of overexposure. Vapors, while low in toxicity, are capable of causing fainting.

WARRANTY INFORMATION

Our only obligation shall be to replace or pay for any adhesive proved defective. Beyond the purchase price of materials supplied by us, we assume no liability for direct, indirect or consequential damages of any kind, and the user accepts the product "as is" and without warranties, expressed or implied. The suitability of the product for a particular purpose or intended use shall be solely up to the user. Shelf life is one year from the manufacturing date according to the batch lot number on each container. Registered trademark of respective manufacturer. For further information contact Shaw Industries at 1-800-441-7429.

SHAW 8300

MATERIAL SAFETY DATA SHEET

SECTION I IDENTIFICATION

Manufactured For: Shaw Industries
Address/Phone: PO Box 2128
Dalton, GA 30722
877.502.7429
Emergency Phone No.: 800.535.5053
Manufacturer's Code Identification: 8300
Trade Name: Shaw 8300 One Floor Solvent-Free Carpet
Seam Sealer
Date Revised: 02/13/08

SECTION II HAZARDOUS INGREDIENTS

None per OSHA Regulation: 29 CFR 1910.1200
SARA Title III Section 313 Chemicals: None
NFPA **HMIS**
 H = 1
 F = 0
 R = 0

SECTION III PHYSICAL DATA

Boiling Point: 212° F
Evaporation Rate/Vapor Density: Same as water
Vapor Pressure: Same as water
LBS/GAL: 8.6 – 9.0
Percent Solids: 45 – 50 (by weight)
Odor: Mild
Color: White
Grams V.O.C. per liter of material: Negligible

SECTION IV FIRE AND EXPLOSION HAZARD DATA

DOT Category: Not regulated
Flash Point: None
LEL: N/A
Extinguishing Media: None required.
Unusual Fire and Explosion Hazards: None.
Special Fire Fighting Procedures: None.

SECTION V HEALTH HAZARD DATA

Symptoms of Over Exposure

Eyes: May cause mild irritation.
Skin: None known.
Inhalation: None known.
Ingestion: None known.

First Aid Procedures:

Eyes: Flush with water
Skin: Wash with soap and water
Inhalation: Remove to fresh air if needed
Ingestion: Do not induce vomiting. Call physician immediately

SECTION VI REACTIVITY DATA

Stability: Stable.
Conditions to avoid: None known.
Incompatibility: None known.
Hazardous decomposition products: None known.
Hazardous polymerization: Will not occur.

SECTION VII SPILL OR LEAK PROCEDURES

Steps to Be Taken if Material is Spilled: Use absorbent materials to collect residue and place into closed container for disposal. Contain with dike to prevent entry to sewers and waterways to prevent blockage due to polymer deposits.

Waste Disposal: Abide by all State, Federal and local regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

Respiratory protection: None should be needed.
Ventilation: Local exhaust
Protective gloves: Chemical resistant gloves
Eyes: Goggles
Other protective equipment: None.

SECTION IX SPECIAL PRECAUTIONS

Precaution for Handling and Storing: Do not puncture, protect from freezing and excessive heat

KEEP OUT OF REACH OF CHILDREN

