

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.**W. F. Taylor Co., Inc.**

11545 Pacific Avenue
Fontana, CA 92337-8228
951/360-6677
CHEMICAL EMERGENCY HOTLINE 1-800-535-5053

PRODUCT NAME: **Envirotec 2075 Seam Sealer**
ITEM NUMBER: 2075-04
ITEM DESCRIPTION: 2075 Envirotec 2075 Seam Sealer Qts
PRODUCT DESCRIPTION: LATEX BASED ADHESIVE
CHEMICAL FAMILY: LATEX POLYMER MIXTURE
REVISION DATE: 12/21/10

HMIS HAZARD RATING

LEAST: 0	HEALTH: 1
SLIGHT: 1	FLAMMABLE: 0
MODERATE: 2	REACTIVITY: 0
HIGH: 3	
EXTREME: 4	

PREPARED BY: ROBERT DDAMULIRA
PREEMPTS PREVIOUS MSDS SHEETS

SECTION II HAZARDOUS INGREDIENTS

<u>COMPONENT/CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>% WT</u>	<u>NOTES</u>
NO HAZARDOUS INGREDIENTS PER CURRENT OSHA REGULATIONS				

SECTION III PHYSICAL DATA

BOILING POINT: 212 DEGREES F
LBS / GALLON: 8.3 - 8.6
EVAPORATION RATE: SAME AS WATER
VAPOR DENSITY: SAME AS WATER
VAPOR PRESSURE: SAME AS WATER
PERCENT VOLATILE: 46 - 50 (BY WEIGHT)
COLOR: OFF WHITE
ODOR: SLIGHT AMMONIA-LIKE ODOR

SECTION IV FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY: NOT REGULATED
FLASH POINT: NONE LEL: NA
EXTINGUISHING MEDIA: NONE REQUIRED
UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE
SPECIAL FIRE FIGHTING PROCEDURES: NONE

SECTION V HEALTH HAZARD IDENTIFICATION

SYMPTOMS OF OVER EXPOSURE:
INHALATION: NONE KNOWN
EYES: MAY CAUSE MILD IRRITATION
SKIN: NONE KNOWN
INGESTION: NONE KNOWN

FIRST AID PROCEDURES:
EYES: FLUSH WITH WATER
SKIN: WASH WITH SOAP AND WATER
INHALATION: REMOVE TO FRESH AIR IF NEEDED

PRODUCT NAME: **Envirotec 2075 Seam Sealer**
ITEM NUMBER: 2075-04
ITEM DESCRIPTION: 2075 Envirotec 2075 Seam Sealer Qts
REVISION DATE: 12/21/10

INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY.

SECTION VI REACTIVITY DATA

STABILITY: STABLE
CONDITIONS TO AVOID: NONE KNOWN
INCOMPATIBILITY-MATERIALS TO AVOID: NONE KNOWN
HAZARDOUS DECOMPOSITION PRODUCTS: NONE KNOWN
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED
KEEP OUT OF SEWER SYSTEMS TO PREVENT BLOCKAGE DUE TO POLYMER DEPOSITS. USE ABSORBENT MATERIAL TO COLLECT AND/OR SCRAPE UP EXCESS AND PLACE INTO CLOSED DOT APPROVED CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL: ABIDE BY ALL STATE, FEDERAL AND LOCAL REGULATIONS.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NONE NEEDED
VENTILATION: LOCAL EXHAUST
PROTECTIVE GLOVES: NONE REQUIRED
EYES: GOGGLES
OTHER PROTECTIVE EQUIPMENT: NONE

SECTION IX SPECIAL PRECAUTIONS

PRECAUTION FOR HANDLING AND STORING: DO NOT PUNCTURE.
KEEP OUT OF THE REACH OF CHILDREN.
PROTECT FROM FREEZING
CAUTION: DO NOT TAKE INTERNALLY. IF SWALLOWED, DO NOT INDUCE VOMITING, CALL PHYSICIAN IMMEDIATELY.

SECTION X TOXICOLOGICAL PROPERTIES

CHRONIC/SUBCHRONIC DATA:
FORMALDEHYDE IS A MINOR VOLATILE COMPONENT OF THIS PRODUCT. RECENT TEST RESULTS HAVE SHOWN FORMALDEHYDE TO CAUSE CANCER IN LABORATORY ANIMALS. FORMALDEHYDE IS READILY DETECTED BY ITS IRRITANT PROPERTIES. THE ODOR DETECTION LEVEL VARIES WITH INDIVIDUALS BETWEEN 0.2 PPM TO 1 PPM. ALSO ACCLIMATION OCCURS FROM REPEATED EXPOSURE BUT SENSITIVITY RETURNS FOLLOWING REST PERIODS AWAY FROM ATMOSPHERES CONTAINING FORMALDEHYDE. WHETHER RISK EXISTS AT LEVELS BELOW THE ODOR THRESHOLD HAS NOT BEEN DETERMINED.

SECTION XI REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD(29CFR 1910.1200)HAZARD CLASS(ES): NONE
SARA TITLE III SECTION 312 HAZARD CLASS: NONE
EPA SARA TITLE III SECTION 313: NONE

ALL COMPONENTS OF THIS PRODUCT ARE EITHER LISTED OR EXEMPT IN THE US EPA TSCA LIST

CALIFORNIA PROPOSITION 65: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR REPRODUCTIVE HARM.

PRODUCT NAME: **Envirotec 2075 Seam Sealer**
ITEM NUMBER: 2075-04
ITEM DESCRIPTION: 2075 Envirotec 2075 Seam Sealer Qts
REVISION DATE: 12/21/10

NOTICE

W.F. TAYLOR BELIEVES THE DATA SET FORTH HEREIN ARE ACCURATE AS OF THE DATE
HEREOF. TAYLOR MAKES NO WARRANTY WITH RESPECT THERETO AND EXPRESSLY DISCLAIMS ALL
LIABILITY FOR RELIANCE THEREON. SUCH DATA ARE OFFERED SOLELY FOR YOUR CONSIDERATION,
INVESTIGATION AND VERIFICATION.
