

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.**W. F. Taylor Co., Inc.**

11545 Pacific Avenue
Fontana, CA 92337-8228
951/360-6677
CHEMICAL EMERGENCY HOTLINE 1-800-535-5053

PRODUCT NAME: **2903 Pressure Sensitive Adh Spray Grade Base**
ITEM NUMBER: 2903-4
ITEM DESCRIPTION: Pressure Sensitive Adh 4-gal
PRODUCT DESCRIPTION: Low Viscosity Latex Based Adhesive
CHEMICAL FAMILY: Acrylic Polymer Blend
REVISION DATE: 12/21/10

HMIS HAZARD RATING

LEAST: 0 HEALTH: 1
SLIGHT: 1 FLAMMABLE: 0
MODERATE: 2 REACTIVITY: 0
HIGH: 3
EXTREME: 4

PREPARED BY: ROBERT DDAMULIRA
PREEMPTS PREVIOUS MSDS SHEETS

SECTION II HAZARDOUS INGREDIENTS

<u>COMPONENT/CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>% WT</u>	<u>NOTES</u>
NO HAZARDOUS INGREDIENTS PER CURRENT OSHA REGULATIONS				

SECTION III PHYSICAL DATA

BOILING POINT: 212 Degrees F
LBS / GALLON: 8.0 - 9.0
EVAPORATION RATE: same as water
VAPOR DENSITY: same as water
VAPOR PRESSURE: same as water
PERCENT VOLATILE: 40 -42 (By weight)
COLOR: white
ODOR: mild

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT, PENSKY-MARTIN C.C.: > 300 F
AUTO IGNITION TEMPERATURE, DEGREES F: NA
FLAMMABLE LIMITS IN AIR (% BY VOLUME): LEL: NA UEL: NA
EXTINGUISHING MEDIA:

(X) Water Fog () Carbon Dioxide () OTHER
(X) Foam (X) Dry Chemical

SPECIAL FIRE FIGHTING PROCEDURES: Use Self Contained Breathing Apparatus and turn out gear.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known

PRODUCT NAME: **2903 Pressure Sensitive Adh Spray Grade Base**
ITEM NUMBER: 2903-4
ITEM DESCRIPTION: Pressure Sensitive Adh 4-gal
REVISION DATE: 12/21/10

SECTION V HEALTH HAZARD IDENTIFICATION

EFFECTS OF ACUTE OVER EXPOSURE:

INHALATION: May cause respiratory irritation

EYES: May cause irritation

SKIN: May cause irritation

INGESTION: May cause gastric disturbance

HEALTH EFFECTS OR RISK FROM EXPOSURE:

ACUTE: May cause eye, skin, respiratory and gastric irritation

CHRONIC: not known

FIRST AID PROCEDURES:

EYES CONTACT: Wash with running water at least 15 minutes. If irritation persists, seek medical attention.

SKIN CONTACT: Remove from skin and wash affected area with soap and water. If irritation persists, seek medical attention.

INHALATION: Move to fresh air. Administer oxygen if necessary. Seek immediate medical attention.

INGESTION: If swallowed, dilute with water. DO NOT INDUCE VOMITING. Never give fluids or induce vomiting to unconscious victim. Get immediate medical attention.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known.

SECTION VI REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Protect from freezing, excessive heat.

INCOMPATIBILITY (MATERIALS TO AVOID): Metal salts will coagulate the product.

HAZARDOUS DECOMPOSITION PRODUCTS (INCLUDING COMBUSTION PRODUCTS): Oxides of Carbon, nitrogen, and organic compounds of unknown structure.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED

Keep out of sewer systems and waterways. Use absorbent materials to collect and / scrape up excess material and collect into closed DOT approved containers for disposal.

WASTE DISPOSAL: Abide by all State, Federal, and Local regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

VENTILATION AND ENGINEERING CONTROLS: Use local exhaust. Do not use closed circulating system. Open windows and doors as necessary.

RESPIRATORY PROTECTION: NIOSH respirator as necessary.

PROTECTIVE GLOVES: Chemical resistant gloves

EYE PROTECTION: Chemical goggles

OTHER CLOTHING AND EQUIPMENT: Use coveralls, apron and boots as necessary to prevent contact. If clothing becomes contaminated, remove and launder before use.

WORK PRACTICES, HYGIENIC PRACTICES: Follow label instructions.

OTHER HANDLING AND STORAGE REQUIREMENTS: Protect against physical damage. Store in cool, dry place (50-90F). Keep away from heat and sparks.

PROTECTIVE MEASURES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: Use goggles and gloves when cleaning equipment. Maintain proper ventilation.

PRODUCT NAME: **2903 Pressure Sensitive Adh Spray Grade Base**
ITEM NUMBER: 2903-4
ITEM DESCRIPTION: Pressure Sensitive Adh 4-gal
REVISION DATE: 12/21/10

SECTION IX SPECIAL PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN. DO NOT INDUCE VOMITING IF INGESTED. AVOID BREATHING BUILDUP OF VAPORS. USE WITH ADEQUATE VENTILATION.

SECTION X TOXICOLOGICAL PROPERTIES

CHRONIC/SUBCHRONIC DATA:

Residual amounts of Vinyl acetate may be contained in this product. ACGIH evaluated vinyl acetate as an A3 (animal carcinogen). Available evidence suggests that the agent is not likely to cause cancer in humans except under common or unlikely routes of exposure. International Agency for research of cancer (IARC) published a monograph of vinyl acetate (1995) which indicates "There is inadequate evidence in humans for carcinogenicity of vinyl acetate" Because vinyl acetate is metabolized to acetaldehyde which is IARC 2B classification (possible carcinogen to human) it is also listed under 2B.

SECTION XI REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD (29CFR 1910.1200) HAZARD CLASS(ES): None
SARA TITLE III SECTION 312 HAZARD CLASS: None
EPA SARA TITLE III SECTION 313: None
CALIFORNIA PROPOSITION 65: This product contains chemicals known to the State of California to cause cancer / and or reproductive harm.

SECTION XII SHIPPING DATA

D.O.T. PROPER SHIPPING NAME (49CFR 172.101-102): NONE
HAZARDOUS SUBSTANCE (49CFR CERCLA LIST): NO RQ: N/A
D.O.T. HAZARD CLASSIFICATION (49CFR 172.101-102):
PRIMARY: NONE SECONDARY: NONE
D.O.T. LABELS REQUIRED (49CFR 172.101-102): NONE
D.O.T. PLACARDS REQUIRED (CFR 172.504): NONE
POISON CONSTITUENT (49CFR 172.203(K)): NONE
BILL OF LADING DESCRIPTION: ADHESIVE CEMENT, NOI
UN/NA CODE: N/A

NOTICE

W.F. TAYLOR BELIEVES THE DATA SET FORTH HEREIN ARE ACCURATE AS OF THE DATE HEREOF. TAYLOR MAKES NO WARRANTY WITH RESPECT THERETO AND EXPRESSLY DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. SUCH DATA ARE OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION.
