



Specifier's Guide to **SHAW** LABEL ADHESIVE PRODUCTS

Distributed By:



CARPET FLOORING ADHESIVES



Available in 4 gallon pails

SHAW 1000 SUPERIOR GRADE CARPET ADHESIVE

Fast-tacking, solvent-free, ultra premium adhesive for installing both direct glue down and double glue down commercial carpets and cushion. Specially designed to provide quick grab with fast wet suction and holding power for bonding the most difficult to install carpet backing. GREENGUARD® and CRI Green Label Plus® certified for low VOC and good indoor air quality.

Maximum Moisture and pH Levels: **CaCl₂ Max. 5 lbs** **RH Max. 90%** **pH Range 5 to 9** **S T**



Available in 4 gallon pails

SHAW 1036 SUPERIOR GRADE ADHESIVE WITH FLOARSEPT®

Fast tacking solvent free ultra premium adhesive with extra antimicrobial protection for both direct glue down and double stick commercial carpets. GREENGUARD® and CRI Green Label Plus® certified for low VOC and good indoor air quality.

Maximum Moisture and pH Levels: **CaCl₂ Max. 5 lbs** **RH Max. 90%** **pH Range 5 to 9** **S T**



Available in 4 gallon pails

SHAW 2001 PREMIUM GRADE CARPET ADHESIVE

Solvent free, non-flammable, latex-based adhesive specially formulated for the interior installation of direct glue down carpets, and a wide range of carpet backings except those with vinyl backs. Not recommended for non-porous backed carpets, patterned carpet installations, or carpet to cushion in a double stick installation. GREENGUARD® and CRI Green Label Plus® certified for low VOC and good indoor air quality.

Maximum Moisture and pH Levels: **CaCl₂ Max. 5 lbs** **RH Max. 90%** **pH Range 5 to 9** **S T**



Available in 4 gallon pails

SHAW 2057 COMMERCIAL PATTERNED CARPET ADHESIVE

Fast tacking superior adhesive for installing all non-vinyl commercial patterned carpet in both direct glue down and double stick applications on approved substrates. Designed to have extended open time to simplify pattern carpet installations that require extensive repositioning of carpet to correct bow, skew and elongation. GREENGUARD® and CRI Green Label Plus® certified for low VOC and good indoor air quality.

Maximum Moisture and pH Levels: **CaCl₂ Max. 5 lbs** **RH Max. 85%** **pH Range 5 to 9** **S T**



Available in 4 gallon pails

SHAW 2081 TUFF LOK X-LINK CARPET ADHESIVE

Advanced cross-linking resin blend adhesive for the interior installation of commercial direct glue down and double stick carpet installations over approved substrates. Formulated to achieve a permanent installation and features a waterproof cured bond. GREENGUARD® and CRI Green Label Plus® certified for low VOC and good indoor air quality.

Maximum Moisture and pH Levels: **CaCl₂ Max. 8 lbs** **RH Max. 90%** **pH Range 5 to 9** **S**



Available in 4 gallon pails

SHAW 2082 TUFF LOK X-LINK CARPET TILE ADHESIVE

Pressure sensitive adhesive specifically formulated for the interior installation of vinyl backed carpet & carpet tile, solid vinyl tile and approved carpet pad to subfloor in double stick installations. May be used dry for removable installation, or wet for permanent installation. Features a waterproof cured bond. GREENGUARD® and CRI Green Label Plus® certified for low VOC and good indoor air quality.

Maximum Moisture and pH Levels: **CaCl₂ Max. 8 lbs** **RH Max. 90%** **pH Range 5 to 9** **S**



Available in 4 gallon pails

SHAW 3600 ECOWORX PERFORMANCE BROADLOOM CARPET ADHESIVE WITH FLOARSEPT®

Extremely high solids, high strength, and fast grabbing carpet adhesive formulated to provide fast grab and wet adhering properties for installation of Shaw Ecoworx Performance Broadloom Carpet. GREENGUARD® and CRI Green Label Plus® certified for low VOC and good indoor air quality.

Maximum Moisture and pH Levels: **CaCl₂ Max. 5 lbs** **RH Max. 85%** **pH Range 5 to 9** **S T**



Available in 4 gallon pails

SHAW 5000 PRESSURE SENSITIVE ADHESIVE

Pressure sensitive adhesive specifically formulated for the interior installation of vinyl backed carpet & carpet tile, solid vinyl tile and approved carpet pad to subfloor in double stick installations. May be used dry for removable installation, or wet for permanent installation. GREENGUARD® and CRI Green Label Plus® certified for low VOC and good indoor air quality.

Maximum Moisture and pH Levels: **CaCl₂ Max. 8 lbs** **RH Max. 90%** **pH Range 5 to 9** **S T**

RESILIENT FLOORING ADHESIVES



Available in 4 gallon, 1 gallon
& 1 quart pails

SHAW 200 TPS ADHESIVE FOR LUXURY VINYL TILE & PLANK

Advanced resin based, cross-linking transitional pressure sensitive adhesive for installations of luxury vinyl tile & plank, solid vinyl tile & plank, vinyl composition tile, vinyl backed sheet goods, and tile-over-tile applications. Features highly aggressive peel strength and transitions to high shear strength bonds. Use over both porous and non-porous substrates, and over radiant heated subfloors. GREENGUARD® and CRI Green Label Plus® certified for low VOC and good indoor air quality. Shaw 200 is specified for installation of Shaw Array Luxury Vinyl Tile & Plank.

Maximum Moisture and pH Levels: **CaCl₂ Max. 8 lbs** **RH Max. 90%** **pH Range 5 to 9** **S**



Available in 4 gallon, 1 gallon
& 1 quart pails

SHAW 350 PRESSURE SENSITIVE ADHESIVE

Clear set solvent free pressure sensitive adhesive for installations of fiberglass backed sheet goods over approved substrates, both porous and non-porous, and over radiant heated substrates. May be used “dry” for removable installations, or “wet” for permanent installations. GREENGUARD® and CRI Green Label Plus® certified for low VOC and good indoor air quality. Shaw 350 is specified for installation of Shaw Dura Tru Resilient Fiberglass Backed Sheet Flooring.

Maximum Moisture and pH Levels: **CaCl₂ Max. 5 lbs** **RH Max. 85%** **pH Range 5 to 9** **S**



Available in 4 gallon pails

SHAW 4030 CLEAR VCT ADHESIVE

Clear set, solvent free, pressure sensitive adhesive made for the interior installation of asphalt and vinyl composition tile (VCT) and closed-cell foam-back hardwood parquet over approved substrates. Formulated to be fast drying for quick installation. GREENGUARD® and CRI Green Label Plus® certified for low VOC and good indoor air quality.

Maximum Moisture and pH Levels: **CaCl₂ Max. 5 lbs** **RH Max. 90%** **pH Range 5 to 9** **S T**

WOOD FLOORING ADHESIVES



Available in 3.5 gallon pails

SHAW 3-IN-1 MS PREMIER WOOD FLOORING ADHESIVE

One component 100% solids cross-linking modified silane polymer adhesive for installation of all types of engineered & solid wood flooring, including exotics, parquet, and bamboo flooring. Product has excellent concrete moisture inhibition capability and good sound reduction property as well as being an outstanding installation adhesive. GREENGUARD® certified for low VOC and good indoor air quality. Shaw 3-in-1 is specified for all Shaw brand hardwood products.

Maximum Moisture and pH Levels: **CaCl₂ Max. 10 lbs** **RH Max. 85%** **pH Range 5 to 9** **S**



Available in 4 gallon, 1 gallon
& 1 quart pails

SHAW 70 WOOD FLOORING ADHESIVE

High solids cross-linking resin based adhesive for interior installation of engineered wood flooring. GREENGUARD® certified for low VOC and good indoor air quality. Shaw 70 is specified for installation of Shaw brand engineered wood flooring.

Maximum Moisture and pH Levels: **CaCl₂ Max. 3 lbs** **RH Max. 75%** **pH Range 5 to 9** **S**

SEAM SEALERS - SUNDRY PRODUCTS



Available in 1 quart

SHAW 4000 CARPET SEAM ADHESIVE **S T**

Non-flammable seaming sealer recommended for seaming all types of cushion-back carpet except vinyl backed. Can also be used to seal cut edges of carpet to prevent raveling. GREENGUARD® and CRI Green Label Plus® certified for low VOC and good indoor air quality.



Available in Pints

SHAW 4062 PREMIUM SEAM SEALER **S**

Solvent Free sealer for seaming fiberglass backed sheet goods in direct glue down installations. GREENGUARD® and CRI Green Label Plus® certified for low VOC and good indoor air quality. Shaw 4062 is specified for seaming Shaw Dura Tru Resilient Fiberglass Backed Sheet Flooring.



Available in Pints

SHAW 8300 VINYL SEAM ADHESIVE **S T**

Solvent free non-flammable latex polymer seam sealer for seaming all thermoplastic backed carpets. GREENGUARD® and CRI Green Label Plus® certified for low VOC and good indoor air quality.

OTHER SUNDRY PRODUCTS



Available in 4 gallon & 30 oz cart.

SHAW 4040 COVE BASE ADHESIVE **S T**

Off-white hard-setting, acrylic adhesive formulated for the installation of rubber and vinyl cove base over wood, concrete, brick, plaster, wallboard or other porous surfaces. Exhibits fast tack and wet suction to hold on inner and outer corners. Will not contribute to staining, shrinkage or plasticizer migration. GREENGUARD® certified for low VOC and good indoor air quality.



Available in 2.5 gallon pails

SHAW 9000 FLOOR SHIELD BARRIER COAT

Multi-functional two-component, solvent-free, water based epoxy barrier coating specifically engineered for use as an adhesive encapsulator over pre-existing adhesive residue. Provides an excellent barrier coating over residue from cutback adhesives, multi-purpose adhesives, and pressure sensitive adhesives, with long term water and humidity resistance, as well as good solvent, chemical and corrosion resistance. GREENGUARD® and CRI Green Label Plus® certified for low VOC and good indoor air quality.

Maximum Moisture and pH Levels: **CaCl₂ Max. 5 lbs** **RH Max. 85%** **pH Range 5 to 9** **S T**



Available in 4 gallon pails

SHAW 9050 pH BLOCKER/FLOOR PRIMER **S T**

Multi-functional acrylic latex solution designed to neutralize excess alkalinity on cementitious surfaces and for use as a primer coat on concrete, plywood, floor patch, acoustical concrete and other porous surfaces, to prevent over absorption of adhesives and to insure a better bond of the adhesive to the subfloor. GREENGUARD® and CRI Green Label Plus® certified for low VOC and good indoor air quality.

Both CaCl₂ MVT and RH tests must be performed in accordance with ASTM F-1869 and ASTM F-2170. MVER and RH tests must be performed indicating diminishing results over time.

Flooring manufacturers (non-Shaw) moisture limitations supersede all other recommendations. To obtain Shaw's Installation Guidelines, specifications, and MSDS contact Shaw Contract 877.502.7429 or visit shawcontractgroup.com